

Technical Specifications

- Physical**
 - 1U 19-inch rack mount
 - 1.7 x 17.2 x 30.6 in (4.3 x 43.7 x 77.7 cm)
- Connectivity**
 - 4 x 100GBASE-LR4 QSFP28
- Performance**
 - Over 560Mpps spread across 4 x 100GbE ports
 - Amplify up to 16 million flows per single PCAP file
- Control**
 - Telesoft Triton CWS GUI
 - TReX interface
 - RestAPI for integration with automated test
- TReX**
 - Supports TReX yaml config file
- Power Stats**
 - 300W typical, and 400W peak

Hardware



Order Options

Part Number	Description
500003096	400G Triton CWS, 1U, 4 x 100GbE, QSFP28

Headquarters
 Telesoft Technologies Ltd
 Observatory House, Stour Park
 Blandford DT11 9LQ UK
 t. +44 (0)1258 480880
 f. +44 (0)1258 486598
 e. sales@telesoft-technologies.com

Americas
 Telesoft Technologies Inc
 430 National Business Parkway
 Suite 480, Annapolis Junction
 MD 20701
 USA
 e. salesusa@telesoft-technologies.com

Asia
 Telesoft Technologies Ltd
 Tapasya Corp Heights
 Ground Floor, Sector 126
 Noida, 201301
 t. +91 120 612 7725
 e. salesindia@telesoft-technologies.com

Telesoft Technologies, the Telesoft Technologies logo design, ThinkEngine, Triton, HINTON, OKEFORD, TDAPI, MPAC, MILBORNE, C-CURE and ARNE are trademarks or registered trademarks of Telesoft Technologies Ltd or its subsidiaries. All other brand or product names may be trademarks of their respective companies. All rights reserved.